



KP Series

POS Terminal

The KP POS terminal is mainly designed for hospitality market. With its rich interface ports, integrated options and especially its highly stable construction, the KP series is recommended for operation in any harsh environment.



Easy Maintenance



Dual LCD creates interactive display



Splash-resistant on frontal



Multiple I / O ports for peripheral connection



MSR / SCR and i-Button optional



WiFi optional



0°~90° Viewing angle



Specification

Model Name	KP-5364	KP-5374	KP-5660	KP-5662	KP-5664	KP-5666
Main board	IAT1-2550	IAT1-1037	IVP-76HM			
CPU	Intel Atom D2550 Dual Core 1.8GHz	Intel Celeron 1037U Dual core 1.8 GHz	Pentium B960 2.2GHz	i3 3110M 2.4GHz	i5 2540M 2.6GHz	i7 3630QM 3.4GHz
Chipset	Intel NM10 Express Chipset	Intel NM70 Chipset	Intel HM76 Express Chipset			
Main Memory	1G DDRIII RAM					
Display Size	15" TFT-LCD with Touch Panel					
Display Resolution	1024 x 768					
Touch Panel	5 Wire Resistive Touch					
HDD	2.5" SATA 320G					
Slot	1 x Mini PCIe , 1 x PCIe					
OS Support	POSReady 2009, POSReady7, Windows XP / XPE, Windows 7, Windows 8 (KP-5374 / KP-5660 / KP-5662 / KP-5664 / KP-5666), Linux					
Power	AC 100V~240V / 60W Power Adapter			AC 100V~240V / 90W Power Adapter		
External I/O Interface						
Serial Port	4 x External COM Port with 5V/12V selectable					
Cash Drawer Port	1 x RJ11 with DC 12V (Default) / 24V					
Parallel Port	1 x DB-25 Female	-				
Keyboard Port	-	1 x PS / 2 (Keyboard or Mouse)				
VGA Port	1 x DB15 VGA					
Speaker	2 x Integrated 1.5 W Stereo Speaker					
Ethernet Port	1 x RJ45 10M / 100M / 1G Base-T					
USB Port	5 x USB 2.0 Type A			3 x USB 2.0 Type A / 2 x USB 3.0 Type A		
DC Output	1 x 12V / 2A DC Jack					
Optional Peripheral						
Magnetic Card Reader	ISO 7811 option 1 / 2 / 3 track					
Finger Print	512dpi x 8bit gray scale, Capture area: 14.6 x 18.1 mm					
i-button	Dallas Key					
Wireless LAN	802.11 b / g					
Customer Display	VFD / LCD Customer Display					
Second Display	TFT-LCD Display / non-Touch					
Control / Indicator						
LED Indicators	2 (HDD / Power)					
Environment						
EMC & Safety	CE / FCC Class A					
Operating Temperature	5°C ~ 40°C					
Storage Temperature	-20°C ~ 60°C					
Operating Humidity	15%~80% RH					
Storage Humidity	20% ~90% RH					
Mechanical						
Housing Color	Cool White, Dark Gray					
Construction	ABS + SECC					
Dimension (W x D x H)	390 x 235 x 320 mm					
Weight (N.W.)	8.5 kg					

• Product specification is subject to change without prior notice.

POS Accessories



Authorized Distributor/Reseller

Appostar

