



NP Series

Multi Function POS

The RP POS terminal saves your effort connecting the printer and keeps the counter clean and clear. with its quick-swap design, the printer module can be maintained in simple steps and is therefore the best solution for space-conscious environment.



Easy Maintenance



Space Saving



Splash-resistant on frontal



Multiple I / O ports for peripheral connection



Drop-in paper loading



MSR / SCR and i-Button optional



0°~90° Viewing angle



LINE ID : NIPPO1314

## Specification

Model Name	NP-7260	NP-7262
Main board	IAT1-2550	IAT1-1037
CPU	Intel Atom D2550 1.8GHz Dual Core	Intel Celeron 1037U 1.8 GHz Dual core
Chipset	Intel NM10 Express Chipset	Intel NM70 Chipset
Main Memory	1GB DDRIII RAM	
Display Size	15" LCD with touch panel	
Display Resolution	1024 x 768	
Touch Panel	5 wire resistive touch	
HDD	2.5" SATA HDD 320G	
Expansion slot	1 x Mini PCIe	
OS Support	POSReady 2009, POSReady7, Windows XP / XPE, Windows 7, Windows 8 (RP-7262) , Linux	
Power	AC 100V~240V / 60W Power Adapter	
<b>External I/O Interface</b>		
Serial Port	4 x External COM Port with 5V / 12V selectable	
Cash Drawer Port	1 x RJ 11 with DC 12V, 1 x RJ 11 with DC 24V	
Keyboard Port	-	1 x PS / 2
VGA Port	1 x VGA (DB15)	
Audio Port	-	1 x Line in, 1x Line out
Speaker	2 x Integrated 1.5 W stereo speaker	
Ethernet Port	1 x RJ45 10M / 100M / 1G Base-T	
Parallel Port	-	1 x Bi-directional Parallel (Standard)
USB Port	4 x USB 2.0 Type A, 5 x USB 2.0 Type A	
DC Output	1 x 12V / 2.5A DC Jack	
Power Button	1 x power on / off switch	
<b>Printer</b>		
Printing Method	Direct Thermal Printing	
Total dots per line	576 dots	
Dot density	8 dots / mm	
Paper width	80 mm	
Printing width	72 mm	
Printing speed	180 mm / s	
Paper loading type	Drop-in easy loading	
Paper feeding pitch	0.0625mm	
<b>Optional Peripheral</b>		
Magnetic Card Reader	ISO 7811 option 1 / 2 / 3 track	
Finger Print	512dpi x 8bit gray scale, Capture area: 14.6 x 18.1 mm	
i-button	Dallas Key	
Wireless LAN	802.11 b / g	
Customer Display	VFD / LCD Customer Display	
Second Display	LCD Display / non-Touch	
<b>Environment</b>		
EMC & Safety	CE / FCC Class A	
Operating Temperature	5°C ~ 40°C	
Storage Temperature	-20°C ~ 60°C	
Operating Humidity	15%~80% RH	
Storage Humidity	20% ~90% RH	
<b>Mechanical</b>		
Housing Color	Black	
Construction	ABS + SECC	
Dimension (W x D x H)	355 x 240 x 390 mm	
Weight (N.W.)	7.1 kg	

• Product specification is subject to change without prior notice.

## POS Accessories



NP-3232(VFD)

NP-5030(LCD)



NP-3280(3'')



NP-2264(2'')



LASER Scanner



MSR



Cash Drawer

Authorized Distributor/Reseller

**nippo**

บริษัท นิปโป เทคโนโลยี (ไทยแลนด์) จำกัด  
74/110 ซ.รามคำแหง 180 แขวงมีนบุรี เขตมีนบุรี  
กรุงเทพมหานคร 10510 โทรศัพท์: 02-518-1314-5 โทรสาร: 02-518-1316

CE FCC Tested To Comply With FCC Standards FOR HOME OR OFFICE USE

RoHS Compliant