



RP Series

Multi Function POS

The RP series fulfills the most applications in space-conscious retail or hospitality, with the quick-swap design printer module for easy maintenance.



Easy Maintenance



Space Saving



Splash-resistant on frontal



Multiple I / O ports for peripheral connection



Drop-in paper loading



MSR / SCR and i-Button optional



0°~90° Viewing angle



Specification

Model Name	RP-7260	RP-7262
Main board	IAT1-2550	IAT1-1037
CPU	Intel Atom D2550 1.8GHz Dual Core	Intel Celeron 1037U 1.8 GHz Dual core
Chipset	Intel NM10 Express Chipset	Intel NM70 Chipset
Main Memory	1GB DDRIII RAM	
Display Size	15" TFT-LCD with touch panel	
Display Resolution	1024 x 768	
HDD	2.5" SATA HDD 320G	
Expansion slot	1 x Mini PCIe	
OS Support	POSReady 2009, POSReady7, Windows XP / XPE, Windows 7, Windows 8 (RP-7262) , Linux	
Power	AC 100V~240V / 60W power adapter	
External I/O Interface		
Serial Port	4 x External COM Port with 5V / 12V selectable	
Cash Drawer Port	1 x RJ 11 with DC 12V, 1 x RJ 11 with DC 24V	
Keyboard Port	--	1 x PS / 2 (Keyboard & Mouse)
VGA Port	1 x VGA (DB15)	
Audio	--	1 x Line in, 1x Line out
Speaker	2 x Integrated 1.5 W stereo speaker	
Ethernet Port	1 x RJ45 10M / 100M / 1G Base-T	
USB Port	4 x USB 2.0 Type A	
DC Output	1 x 12V / 2.5A DC Jack	
Power Button	1 x power on / off switch	
Printer		
Printing Method	Direct Thermal Printing	
Total dots per line	576 dots	
Dot density	8 dots / mm	
Paper width	80 mm	
Printing width	72 mm	
Printing speed	180 mm / s	
Paper loading type	Easy Loading	
Paper feeding pitch	0.0625mm	
Optional Peripheral		
Magnetic Card Reader	ISO 7811 option 1 / 2 / 3 track	
Finger Print	512dpi x 8bit gray scale, Capture area: 14.6 x 18.1 mm	
i-button	Dallas Key	
Wireless LAN	802.11 b / g	
Customer Display	VFD / LCD Customer Display	
Environment		
EMC & Safety	CE / FCC Class A	
Operating Temperature	5°C ~ 40°C	
Storage Temperature	-20°C ~ 60°C	
Operating Humidity	15%~80% RH	
Storage Humidity	20% ~90% RH	
Mechanical		
Housing Color	Black	
Construction	ABS + SECC	
Dimension (W x D x H)	355 x 240 x 390 mm	
Weight (N.W.)	7kg	

• Product specification is subject to change without prior notice.

POS Accessories



Authorized Distributor/Reseller

Appostar

CE FCC Tested To Comply With FCC Standards FOR HOME OR OFFICE USE

RoHS Compliant

13F., No.213, Sec. 3, Beixin Rd., Xindian Dist., New Taipei City 231, Taiwan (R.O.C.)

Tel: 886-2-2910-6168 Fax: 886-2-2910-6199 Email: sales@appostar.com